

Intrinsically safe solution for monitoring waste and non-potable water level.

The PTI, submersible pressure transducer is a cost effective level monitoring solution for monitoring within hazardous environments. Combined with the Cello CSO, Cello I.S. Mk2 and Cello GS3, the PTI provides high accuracy over a wide selection of range options.

Key Features

- Multiple range and cable length options available
- High resolution and accuracy
- Powered by the Technolog data logger
- Certified intrinsically safe for use in hazardous areas (ATEX, Zone 0)
- Submersible pressure transducer, not affected by foam or wind
- Rugged design
- Easy installation





Technical Specifications

Input	- Integrated Submersible Pressure (Depth) Sensor (Gauge type)
Range	- Integrated Submersible Pressure (Depth) Sensor (Gauge type) Standard range: 0 – 5 mH ₂ O gauge with 7m cable <i>(Other pressure ranges and cable length available on request)</i>
Measurement	Accuracy: ±0.2% Full Scale (FS) Best Straight Line (BSL) Resolution: +/- 1mm Response (on) time: 3 seconds
Environmental	Operating temperature: -10°C to +50°C
Intrinsic Safety	Certified Intrinsically Safe: Sira 14ATEX2026X - Ex ia IIB T4 Ga (Note UNIK5000 or PDCR1830 sensor fitted) IECEX SIR 14.0012X - Ex ia IIB T4 Ga (Note UNIK 5000 sensor only) Ambient temperature: -40°C to +60°C
Mechanical	Input cable: 400mm standard, optional = 10m Dimensions (mm): Pressure sensor body - 140 x 25 diameter (Unik 5000), 105 x 17.5 diameter (PDCR 1830)

