

Cello-M is an innovative combined communication and power solution that utilises latest 4G LPWAN technologies for near real time data and network control. Additionally, the Cello-M passes through power to the connected data logger.

- Utilises MQTT publish / subscribe message queuing solution
- Provides advanced communications integration
- Multiple channels transmitted (pressure, temperature, flow, status inputs and operation of differential pressure switches or slam open/close)
- Ultra low power
- User replaceable battery
- User replaceable Sim
- Certified for use in Zone 0 hazardous locations
- Compatible with Technolog's solar energy and battery technology
- Pass through power to connected dataloggers and controllers





Technical Specifications

Communication Protocol	4G LPWAN (NBIoT/LTE-m) 2G IP (MQTT) Speed: 1200-9600 bps GSM Communication Speed: Availability of rate defined by access at a given site, dependent on location
Supply	External (6/12cell): 3.9v Typical battery life 5 years External Solar: Via Technolog Energy Harvesting Interface Supply to VCM: 6.8v
Environmental	Operating ambient temperature: -20°C to +50°C Protection classification: IP68 (1m depth @ 48 hours)
Intrinsic Safety	Certified Intrinsically Safe: Cello M: UKCA Ex / ATEX / IECEx IIC Zone 0 Battery Pack: UKCA Ex / ATEX / IECEx IIC Zone 0
Mechanical	Cello M Dimensions (mm): 270 x 170 x 91 Weight: 0.760 kg (without cable) 0.910 kg (including 2 m cable)

